

MUK440 wzmacniacz



OUTPUT POWER - 20Hz-20kHz, 0.1% THD

@2 Ω	@4 Ω	@8 Ω	Bridge @4 Ω	Bridge @8 Ω
4 x 820 W	4 x 830 W	4 x 530 W	2 x 1640 W	2 x 1660 W

Output Power

Continuous Average Power
 RMS, 1kHz, 1.0% THD+N

@2 Ω	4 x 1000 W
@4 Ω	4 x 1000 W
@8 Ω	4 x 520 W
Bridge @4 Ω	2 x 2000 W
Bridge @8 Ω	2 x 2000 W

Pink Noise 12dB Crest Factor

@2 Ω
@4 Ω
@8 Ω

Frequency Response

Power Bandwidth ±0.25dB	20Hz-20kHz.
-------------------------	-------------

Phase Response

@ 1 watt 20Hz-20kHz

Total Harmonic Distortion

20Hz-20kHz	<0,05%
------------	--------

Damping Factor

20Hz-500Hz @8 Ω	>400
-----------------	------

Intermodulation Distortion

SMPTE	
Crosstalk	
20Hz-20kHz	> 75dB
Voltage Gain	32 dB

Sensitivity

Rated Power @8 Ω

Signal-to-Noise-Ratio

Unweighted
 A weighted

Required AC Mains

230 V - 50 Hz (idle)
@4 Ω (1/8 rated power)
@8 Ω (1/8 rated power)

Dimensions

W x H x D (mm)	483 x 89 x 250
W x H x D (inches)	

Weight

Net	6kg
-----	-----